

AHD kamere i snimači

Full Color - kolor slika i u potpunom mraku 24/7

FC-5350			1/2.8" SONY Starvis Back-illuminated CMOS sensor, kolor slika i u potpunom mraku 24/7 , vodootporna kamera rezolucije 5 megapiksela , AHD/TVI : 5M @ 12.5fps, 4M @ 25fps, 2M @ 25fps, 720P @ 25fps; CVI : 4M / 2M / 720p @ 25fps, CVBS 25fps, 0,005Lux , objektiv 3,6mm ili 6mm , IR-CUT , IP67 , WDR , AI-DNR , Starlight , UTC , 4 led diode warm white 4000K dometa do 40m, nosač sa skrivenom kablazom, napajanje DC12V / 750mA, dimenzije 268(W) x 95(H) x 88(D) mm, težina 1,5kg.	83
---------	---	---	--	----

AHD kamere 1080P FullHD (2Mpix)

LMBM30HTC130S		Longse	1/3" SONY CMOS Sensor, 960P , AHD / TVI / CVI / CVBS mini kamera rezolucije 1.3 megapiksela , 0.1 Lux/F1.2, megapikselni objektiv 3.6mm, DNR, OSD, napajanje DC12V 250mA, dimenzije 30 x 33 x 30mm, težina 150g.	54
---------------	---	---------------	---	----

AHD kamere 4 Mpix

LBP90AD400V			1/3" OmniVision OV4689 CMOS Sensor, AHD vodootporna kamera rezolucije 4 megapiksela , 0,01 Lux / F1.2, varifokalni objektiv 2.8-12 mm, IR-CUT , IP66 , WDR , 3DNR , UTC , OSD , 6 IC diode dometa do 60m, nosač sa skrivenom kablazom, napajanje DC12V / 1000mA, dimenzije 211(W) * 92(H) * 90(D)mm., težina 1400g.	109
LBW30AD400V		Longse	1/3" OmniVision OV4689 CMOS Sensor, AHD vodootporna kamera rezolucije 4 megapiksela , 0,01 Lux / F1.2, megapikselni objektiv 2.8 mm, IR-CUT , IP66 , WDR , 3DNR , UTC , OSD , 2 IC diode dometa do 30m, nosač sa skrivenom kablazom, napajanje DC12V / 700mA, dimenzije 162(W) * 88(H) * 86(D)mm., težina 600g.	75
LIRDCAD400V			1/3" OmniVision OV4689 CMOS Sensor, AHD vodootporna kamera rezolucije 4 megapiksela , 0,01 Lux / F1.2, varifokalni objektiv 2.8-12 mm, IR-CUT , IP66 , WDR , 3DNR , UTC , OSD , 24 IC dioda dometa do 30m, napajanje DC12V / 700mA, dimenzije 93(H) x 131(Φ)mm, težina 800g.	85

AHD kamere 5 Mpix

AC-2250S			1/2.8" SONY Starvis Back-illuminated CMOS sensor, AHD / TVI / CVI / CVBS vodootporna kamera rezolucije 5 megapiksela , AHD : 5M@20fps/12.5fps, 4M@25fps/15fps, 2M@25fps, TVI : 5M@20fps/12.5fps, 4M/2M@25fps, CVI : 5M@20fps, 4M/2M@25fps, megapikselni objektiv 3.6mm, IR-CUT , IP66 , WDR , 3DNR , UTC , OSD , 18 IC dioda dometa do 20m, napajanje DC12V / 550mA, dimenzije 74(H) x 93(Φ)mm, težina 400g.	65
Kućište kamere B220A			Duboka metalna osnova za dome kamere sa fiksnom optikom Ø 9,3cm dubine 4cm za smestaj video baluna, konektora, napajanja ...	9
LIRDNTHTC500ESL			1/2.8" SONY Starvis Back-illuminated CMOS sensor, AHD / TVI / CVI / CVBS vodootporna kamera rezolucije 5 megapiksela , AHD : 5M@20fps/12.5fps, 4M/2M@25fps, TVI : 5M@20fps/12.5fps, 4M/2M@25fps, CVI : 5M@20fps, 4M/2M@25fps, varifokalni objektiv 2.8-12mm, IR-CUT , IP67 , WDR , 3DNR , UTC , OSD , 24 IC dioda dometa do 30m, napajanje DC12V / 750mA, dimenzije Φ120 x 98(H) mm, težina 800g	79
AC-3150S		Longse	1/2.8" SONY Starvis Back-illuminated CMOS sensor, AHD / TVI / CVI / CVBS vodootporna kamera rezolucije 5 megapiksela , AHD : 5M@20fps/12.5fps, 4M/2M@25fps, TVI : 5M@20fps/12.5fps, 4M/2M@25fps, CVI : 5M@20fps, 4M/2M@25fps, varifokalni objektiv 2.8-12mm, IR-CUT , IP67 , WDR , 3DNR , UTC , OSD , 24 IC dioda dometa do 30m, napajanje DC12V / 750mA, dimenzije Φ120 x 98(H) mm, težina 800g	89
Kućište kamere B170			Duboka metalna osnova za dome kamere sa varifokalnom optikom Ø 12cm dubine 4cm za smestaj video baluna, konektora, napajanja ...	11
LIN60HTC500ESL			1/2.8" SONY Starvis Back-illuminated CMOS sensor, AHD / TVI / CVI / CVBS vodootporna kamera rezolucije 5 megapiksela , AHD : 5M@20fps/12.5fps, 4M/2M@25fps, TVI : 5M@20fps/12.5fps, 4M/2M@25fps, CVI : 5M@20fps, 4M/2M@25fps, varifokalni objektiv 2.8-12 mm, IR-CUT , IP67 , WDR , 3DNR , UTC , OSD , 4 IC diode dometa do 40m, nosač sa skrivenom kablazom, napajanje DC12V / 750mA, dimenzije 275(W) * 91(H) * 80(D)mm., težina 1400g.	94

LBE90HTC5005XES L		Longse	1/2.8" SONY Starvis Back-illuminated CMOS sensor, AHD / TVI / CVI / CVBS vodootporna kamera rezolucije 5 megapiksela , AHD: 5M@20fps/12.5fps, 4M/2M@25fps, TVI: 5M@20fps/12.5fps, 4M/2M@25fps, CVI: 5M@20fps, 4M/2M@25fps, motorizovani varifokalni objektiv 2.7-13.5 mm, IR-CUT, IP67, WDR, 3DNR, UTC, OSD, Starlight , 6 IC dioda dometa do 60m, nosač sa skrivenom kablom, napajanje DC12V / 900mA, dimenzije 179(W) x 90(H) x 90(D)mm, težina 1400g.	101
B245			Metalni zidni G-nosač, dimenzije 245(W) x 160(D) x 163(H)mm, težina 2.1kg. Kompatibilan sa modelima: LVDB, LVDH, LVDC45, LIRAB, LVWDB20, LVWDC20, LIRDC, LIRDCA, LIRDNT, LMDC	26
B131			Univerzalna dozna za kamere. Razvodna kutija namenjena za spoljnu montažu. Mogućnost smeštanja konektora za povezivanje. Dimenzija dozne 131x131x51 mm.	5.2
Plastično plafonsko podnožje			Univerzalna duboka plastična osnova za dome kamere, dimenzija Ø14cm i dubine 3.7cm za smestaj video baluna, konektora, napajanja ...	3.2
Kućište kamere B200			Duboka metalna osnova za bullet kamere Ø 12cm dubine 4cm, pogodna za smestaj video baluna, konektora, napajanja ...	11
AHD kamere 8 Mpix				
AC-2180		AVICOM video security	1/2.8" SONY IMX415 CMOS sensor, AHD / TVI / CVI vodootporna kamera rezolucije 8 megapiksela, AHD : 4K@15fps, 4M / 2M@30fps, TVI : 4K@15fps, 4M / 2M@30fps; CVI : 4K@15fps, 4M / 2M@30fps, megapikselni objektiv 3.6mm, IR-CUT, IP67, WDR, 3DNR, UTC, OSD , 18 IC dioda dometa do 20m, napajanje DC12V / 550mA, dimenzije Ø93 x 74(H) mm, težina 400g	79
AC-3180			1/2.8" SONY IMX415 CMOS sensor, AHD / TVI / CVI vodootporna kamera rezolucije 8 megapiksela, AHD : 4K@15fps, 4M / 2M@30fps, TVI : 4K@15fps, 4M / 2M@30fps; CVI : 4K@15fps, 4M / 2M@30fps, motorizovani varifokalni objektiv 3.3-12 mm, IR-CUT, IP67, WDR, 3DNR, UTC, OSD , 24 IC dioda dometa do 30m, napajanje DC12V / 750mA, dimenzije Ø120 x 98(H) mm, težina 800g	116
DAHUA DVR snimači				
XVR1B04-I			Penta-brid video snimač sa 4 analogna kanala plus 1 dodatni ip kanal rezolucije do 2MP. Maksimalna rezolucija snimanja 1080N. Frame rate: 1080N (1~25/30fps). Bandwidth In 20Mbps, Bandwidth Out 20Mbps. Kompresija snimanja: H.265+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. 1HDD maksimalnog kapaciteta 6TB. SMD Plus.	call
XVR1B08-I			Penta-brid video snimač sa 8 analogna kanala plus 2 dodatnih IP kanala rezolucije do 6MP. Maksimalna rezolucija snimanja 2MP. Frame rate: Prvi kanal: 1080N (1fps~25/30fps) ostali kanali: 1080N (1fps~15fps). Bandwidth In 40Mbps, Bandwidth Out 40Mbps. Kompresija snimanja: H.265+; 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. 1HDD maksimalnog kapaciteta 6TB . SMD Plus.	call
XVR1B16-I			Penta-brid video snimač sa 16 analogna kanala plus 2 dodatna ip kanala rezolucije do 6MP. Maksimalna rezolucija snimanja 1080N. Frame rate: 1. kanal 1080N (1fps~25/30 fps), ostali 1080N (1fps~15 fps); 960H/D1/HD1/BCIF/CIF (1fps~25/30 fps). Bandwidth In 64Mbps, Bandwidth Out 64Mbps. Kompresija snimanja: H.265+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. 1HDD maksimalnog kapaciteta 16TB. SMD Plus	call
XVR5104HS-I3		dahua TECHNOLOGY	Penta-brid video snimač sa 4 analogna kanala plus 2 dodatnih ip kanala rezolucije do 6MP. AI tehnologija. Maksimalna rezolucija snimanja 5MP. Frame rate: 5M-N (1fps~10fps); 4M-N/1080P (1fps~15fps). Bandwidth In 32Mbps, Bandwidth Out 32Mbps. Kompresija snimanja: H.265+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. RS485 komunikacija. 1HDD maksimalnog kapaciteta 16TB. Face Recognition, Perimeter Protection, SMD Plus.	call
XVR5108HS-I3			Penta-brid video snimač sa 8 analogna kanala plus 4 dodatnih IP kanala rezolucije do 6MP. AI tehnologija. Maksimalna rezolucija snimanja 5MP. Frame rate: 5M-N (1fps~10fps); 4M-N/1080P (1fps~15fps). Bandwidth In 64Mbps, Bandwidth Out 64Mbps. Kompresija snimanja: H.265+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. RS485 komunikacija. 1HDD maksimalnog kapaciteta 16TB. Face Recognition, Perimeter Protection, SMD Plus.	call
XVR5116HS-I3			Penta-brid video snimač sa 16 analogna kanala plus 8 dodatnih ip kanala rezolucije do 6MP. AI tehnologija. Maksimalna rezolucija snimanja 5MP. Frame rate: 5M-N (1fps~10fps); 4M-N/1080P (1fps~15fps). Bandwidth In 128Mbps. Kompresija snimanja: H.265+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 2x USB 2.0, 1x USB 3.0. RS485 komunikacija. 1HDD maksimalnog kapaciteta 16TB po disku. Face Recognition, Perimeter Protection, SMD Plus.	call

HD-TVI kamere i snimači

2Mpix HD-TVI kamere ColorVu - kolor slika u svim uslovima rada

DS-2CE19DF8T-AZE		2MP TVI kamera u bullet kućištu sa ColorVu i PoC tehnologijom 4 u 1 TVI /AHD /CVI /CVBS režim. 0.0003 Lux @ (F1.0, AGC ON), 0 Lux with white Light. Maksimalna rezolucija 1920x1080. Varifokalna optika 2.8 - 12 mm. Nivo zaštite IP68. 130dB WDR. Domet LED dioda 40 metara. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-S. Nosač za banderu je DS-1275ZJ-SUS. Materijal: Metal.	call
DS-2CE10DF3T-FS		2MP TVI kamera u bullet kućištu sa ColorVu tehnologijom 4 u 1 TVI /AHD /CVI /CVBS režim. Color: 0.0005Lux@ (F1.0, AGC ON), 0 Lux with white light. Maksimalna rezolucija 1920x1080. Fiksna optika 3.86 mm. Nivo zaštite IP67. 130dB WDR. Domet LED dioda 20 metara. Integriran mikrofoni. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-XS. Materijal: Metal.	call
DS-2CE12DFT-PIRXOF		2MP TVI kamera u bullet kućištu sa ColorVu tehnologijom 4 u 1 TVI /AHD /CVI /CVBS režim. Color: 0.0005Lux@ (F1.0, AGC ON), 0 Lux with white light. Maksimalna rezolucija 1920x1080. Fiksna optika 3.6 mm. Nivo zaštite IP67. 130dB WDR. Domet LED dioda 40 metara. PIR detektor, strobe light, Integrirana sirena. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-XS. Mat: Met/Plast	call
DS-2CE70DF3T-MFS		2MP TVI kamera u turet kućištu sa ColorVu tehnologijom 4 u 1 TVI / AHD / CVI / CVBS režim, 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with White Light. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Nivo zaštite IP67. 130dB WDR. Domet LED dioda 20 metara. Integriran mikrofoni. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-XS. Nosač za banderu je DS-1275ZJ-SUS. Ugaoni nosač DS-1276ZJ-SUS. Zidni nosač DS-1272ZJ-110-TRS. Materijal: Metal.	call

5Mpix HD-TVI kamere ColorVu - kolor slika u svim uslovima rada

DS-2CE12KF3T-LE (2.8mm)		3K Dual-Light TVI kamera u bullet kućištu sa ColorVu tehnologijom 4 u 1 TVI/AHD/CVI/CVBS režim. 0.0005Lux@ (F1.0, AGC ON), 0 Lux with white light. Maksimalna rezolucija 2960x1665. Fiksna optika 2.8mm. Nivo zaštite IP67. 130dB WDR. Domet IR/LED dioda 40 metara. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-XS. Zidni nosač je DS-2280ZJ. Materijal: Metal .	call
DS-2CE72HFT-F28		5MP TVI kamera u turet kućištu sa ColorVu tehnologijom 4 u 1 TVI / AHD / CVI / CVBS režim. 0.0005Lux@ (F1.0, AGC ON), 0 Lux with white light. Maksimalna rezolucija 2560x1944. Fiksna optika 2.8mm. Nivo zaštite IP67. 130dB WDR. Domet LED dioda 20 metara. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-S. Nosač za banderu je DS-1275ZJ-SUS. Zidni nosač je DS-1272ZJ-TRS. Materijal: Metal i Plastika.	call

HD-TVI kamere 1080P 2Mpix

DS-2CE19D0T-VFIT3F		2MP TVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.01 Lux@(F1.6, AGC ON), 0 Lux with IR. Maksimalna rezolucija 1920x1080. Varifokalna optika 2.7 - 13.5 mm. Nivo zaštite IP67. DWDR. Domet IC dioda 40 metara. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-M. Nosač za banderu je DS-1275ZJ-SUS. Ugaoni nosač je DS-1276ZJ-SUS. Mat: Met/ Plas	call
DS-2CE17D0T-IT3F		2MP TVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR . Maksimalna rezolucija 1920x1080. Fiksna optika 3.6mm. Nivo zaštite IP67. DWDR. Domet IC dioda 40 metara. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-XS. Materijal: Metal i Plastika.	call
DS-2CE17D0T-IT5F		2MP TVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR. Maksimalna rezolucija 1920x1080. Fiksna optika 3.6mm. Nivo zaštite IP67. DWDR. Domet IC dioda 80 metara. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-XS. Materijal: Metal i Plastika.	call
DS-2CE16D0T-ITFS		2MP TVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Nivo zaštite IP67. DWDR. Domet IC dioda 30 metara. Integriran mikrofoni. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-XS. Materijal: Metal.	call
DS-2CE79D0T-VFIT3F		2MP TVI kamera u turet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR. Maksimalna rezolucija 1920x1080. Varifokalna optika 2.7 - 13.5 mm. DWDR. Nivo zaštite IP67. Domet IC dioda 40 metara. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-M. Zidni nosač je DS-1273ZJ-130-T. Materijal: Metal i Plastika.	call
DS-2CE76D3T-ITMF		2MP TVI kamera u turet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.005 Lux@(F1.2, AGC ON), 0 Lux with IR. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Nivo zaštite IP67. 120 dB WDR. Domet IC dioda 30 metara. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-XS. Nosač za banderu je DS-1275ZJ-SUS. Zidni nosač je DS-1272ZJ-110-TRS. Materijal: Metal.	call

DS-2CE76D0T-ITMFS			2MP TVI kamera u turret kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Nivo zaštite IP67. DWDR. Domet IC dioda 30 metara. Integriran mikrofoni. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-XS. Nosač za banderu je DS-1276ZJ-SUS. Ugaoni nosač DS-1276ZJ-SUS. Zidni nosač DS-1272ZJ-110-TRS. Materijal: Metal.	call
DS-2CE76D0T-ITPF (2.8mm)(C)			2MP TVI kamera u turret kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. DWDR. Domet IC dioda 20 metara. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-XS. Nosač za banderu je DS-1275ZJ-SUS. Ugaoni nosač DS-1276ZJ-SUS. Zidni nosač DS-1272ZJ-110-TRS. Materijal: Plastika.	call
Postolje-kutija za kamere B131			Univerzalna dozna za kamere. Razvodna kutija namenjena za spoljnu montažu. Mogućnost smeštanja konektora za povezivanje. Dimenzija dozne 131x131x51 mm.	call
DS-1280ZJ-XS			Razvodna kutija za smeštanje kablova i napajanja. Materijal Aluminum Alloy. Dimenzije $\Phi 100 \times 43.2 \times 129$ mm. Tezina 320g.	call
DS-1280ZJ-S			Razvodna kutija za smeštanje kablova i napajanja. Materijal Aluminum Alloy. Dimenzije $\Phi 137 \times 53.4 \times 164.8$ mm. Tezina 527g.	call
DS-1280ZJ-M			Razvodna kutija za smeštanje kablova i napajanja. Dimenzije $\Phi 157 \times 185 \times 51.5$ mm, težina 621g	call
DS-1258ZJ			Zidni nosač za kameru. Dimenzije $\varnothing 111 \text{ mm} \times 120 \text{ mm} \times 80 \text{ mm}$, 200g	call
HD-TVI kamere 5Mpix				
DS-2CE16H0T-ITPF (3.6mm)(C)			5MP TVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR. Maksimalna rezolucija 2560x1944. Fiksna optika 3.6mm. Nivo zaštite IP67. DWDR. Domet IC dioda 25 metara. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-XS. Materijal: Plastika.	call
DS-2CE16H0T-ITFS			5MP TVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR. Maksimalna rezolucija 2560x1944. Fiksna optika 2.8mm. Nivo zaštite IP67. DWDR. Domet IC dioda 30 metara. Integriran mikrofoni. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-XS. Materijal: Metal.	call
DS-2CE17H0T-IT3F			5MP TVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR. Maksimalna rezolucija 2560x1944. Fiksna optika 3.6mm. Nivo zaštite IP67. DWDR. Domet IC dioda 40 metara. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-XS. Materijal: Metal i Plastika.	call
DS-2CE17H0T-IT5F			5MP TVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR. Maksimalna rezolucija 2560x1944. Fiksna optika 3.6mm. Nivo zaštite IP67. DWDR. Domet IC dioda 80 metara. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-XS. Materijal: Metal i Plastika.	call
DS-2CE19H8T-AIT3ZF			5MP TVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. Color: 0.003 Lux @ (F1.2, AGC ON), 0 Lux with IR. Maksimalna rezolucija 2560x1944. Varifokalna optika 2.7 13.5 mm. Nivo zaštite IP67. 130dB WDR. Domet IC dioda 80 metara. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-S. Nosač za banderu je DS-1275ZJ-SUS. Ugaoni nosač: DS-1276ZJ-SUS. Materijal: Metal.	call
DS-2CE76H0T-ITPF (2.8mm)(C)			5MP TVI kamera u turret kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.01 Lux @ (F2.0, AGC ON), 0 Lux with IR. Maksimalna rezolucija 2560x1944. Fiksna optika 2.8mm. DWDR. Domet IC dioda 20 metara. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-XS. Nosač za banderu je DS-1275ZJ-SUS. Zidni nosač je DS-1272-110-TRS. Materijal: Plastika.	call
DS-2CE76H0T-ITMFS			5MP TVI kamera u turret kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR. Maksimalna rezolucija 2560x1944. Fiksna optika 2.8mm. Nivo zaštite IP67. DWDR. Domet IC dioda 30 metara. Integriran mikrofoni. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-XS. Nosač za banderu je DS-1275ZJ-SUS. Zidni nosač je DS-1272-110-TRS. Materijal: Metal.	call

DS-2CE76H8T-ITMF		HIKVISION®	5MP TVI kamera u turret kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.003 Lux@(F1.6, AGC ON), 0 Lux with IR. Maksimalna rezolucija 2560x1944. Fiksna optika 2.8mm. Nivo zaštite IP67. 130dB WDR. Domet IC dioda 30 metara. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-XS. Nosač za banderu je DS-1275ZJ-SUS. Zidni nosač je DS-1272-110-TRS. Ugaoni nosač je DS-1276ZJ-SUS. Materijal: Metal.	call
HD-TVI kamere 4K - 8Mpix				
DS-2CE16U1T-ITPF			8MP TVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. Color: 0.01Lux@(F1.2, AGC ON), 0 Lux with IR. Maksimalna rezolucija 3840x2160. Fiksna optika 2.8mm. Nivo zaštite IP67. DWDR. Domet IC dioda 30 metara. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-XS. Materijal: Plastika.	call
DS-2CE19U1T-AIT3ZF		4K ULTRA HD	8MP TVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. Color: 0.01Lux@(F1.2, AGC ON), 0 Lux with IR. Maksimalna rezolucija 3840x2160. Varifokalna optika 2.7 - 13.5 mm. Nivo zaštite IP67. DWDR. Domet IC dioda 80 metara. 12v napajanje. Odgovarajuća dozna je DS-1280ZJ-S. Nosač za banderu je DS-1275ZJ-SUS. Materijal: Metal i Plastika.	call
DS-2CE76U1T-ITMF			NOVA 4K ultra low light turret HD-TVI kamera, Rezolucija slike 8.29 Mpix (3840 x 2160)@12.5fps, Mehanički IR filter (ICR), Osetljivost 0.01 LUX (0 Lux sa IR), Ugrađen fiksni objektiv 2.8mm (102.2o); Inteligentna EXIR rasveta dometa do 30 metara (Smart IR), Za unutrašnju/spoljašnju montažu (IP 67), D-WDR funkcija, 3D DNR, Radna temperatura -40°C~60°C; Napajanje 12Vdc/5.3W	call
HD-TVI snimači 4ch				
iDS-7104HQHI-M1/S(E)			Turbo AcuSense video snimač sa 4 analogna kanala i 1 dodatni IP kanal do rezolucije 6MP. Maksimalna rezolucija snimanja 4MP lite. Frame rate: 5 MP @12fps/ 1080p lite@25fps. Total Bandwidth 72Mbps. Kompresija snimanja: GA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. 1HDD maksimalnog kapaciteta 10TB. Human/Vehicle Analysis. Motion Detection 2.0. Facial Detection.	call
iDS-7104HUHI-M1/S(E)		5MP	Turbo AcuSense video snimač sa 4 analogna kanala i 2 dodatna IP kanala do rezolucije 8MP. Maksimalna rezolucija snimanja 8MP. Frame rate: MP@8 fps/ 5MP@12fps/ 3K@12 fps/ 4 MP@15fps/ 3 MP@18fps/ 1080p@25fps. Kompresija snimanja: H.265 Pro+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. 1HDD maksimalnog kapaciteta 10TB. Human/Vehicle Analysis.	call
iDS-7204HQHI-M1/S(C)		HIKVISION®	Turbo AcuSense video snimač sa 4 analogna kanala i 1 dodatni IP kanal do rezolucije 6MP. Maksimalna rezolucija snimanja 4MP lite. Frame rate: 4 MP lite@15fps/1080p lite@25fps. Kompresija snimanja: H.265 Pro+. 1x VGA, 1x HDMI, 1x video out. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. RS-485 komunikacija. 1HDD maksimalnog kapaciteta 10TB. Human/Vehicle Analysis na 2 kanala. Quick search by object or event type is supported.	call
iDS-7204HUHI-M1/S(C)		5MP	Turbo AcuSense video snimač sa 4 analogna kanala i 2 dodatna IP kanala do rezolucije 8MP. Maksimalna rezolucija snimanja 8MP. Frame rate: 8 MP@8fps/ 5MP@12fps/ 3K@12fps/ 4 MP@15fps/ 8 MP Lite@15 fps/ 3 MP@18fps/ 1080p@25fps. Kompresija snimanja: H.265 Pro+. 1x VGA, 1x HDMI, 1x video out. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. RS-485 komunikacija. 1HDD maksimalnog kapaciteta 10TB. Human/Vehicle Analysis na 4 kanala. Quick search by object or event type is supported.	call
iDS-7204HTHI-M1/S(C)		4K ULTRA HD	Turbo AcuSense video snimač sa 4 analogna kanala i 4 dodatna IP kanala do rezolucije 8MP. Maksimalna rezolucija snimanja 8MP. Frame rate: 8MP@15fps/ 3K@20fps / 5M@20 fps/ 4 MP/ 1080p@30fps. Kompresija snimanja: H.265 Pro+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/1000M mrežni interfejs. 1x USB 2.0, 1x USB 3.0. RS-485 komunikacija. 1HDD maksimalnog kapaciteta 10TB. Human/Vehicle Analysis na 4 kanala. Quick search by object or event type is supported.	call
HD-TVI snimači 8ch				
iDS-7108HQHI-M1/S(C)		HIKVISION®	Turbo AcuSense video snimač sa 8 analogna kanala i 2 dodatna IP kanala do rezolucije 6MP. Maksimalna rezolucija snimanja 4MP lite. Frame rate: 4 MP lite@15fps/1080p lite@25fps. Total Bandwidth 96Mbps. Kompresija snimanja: H.265 Pro+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. 1HDD maksimalnog kapaciteta 10TB.	call
iDS-7108HUHI-M1/S(C)			Turbo AcuSense video snimač sa 8 analogna kanala i 4 dodatna IP kanala do rezolucije 8MP. Maksimalna rezolucija snimanja 8MP. Frame rate: 8 MP@8fps/ 5 MP@12fps/ 3K@12 fps/ 4 MP@15fps/ 3 MP@18 fps/ 1080p@25fps. Kompresija snimanja: H.265 Pro+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 2x USB 2.0. 1HDD maksimalnog kapaciteta 10TB. Human/Vehicle Analysis na 4 kanala. Quick search by object or event type is supported.	call

iDS-7208HQHI-M1/S(C)			Turbo AcuSense video snimač sa 8 analogna kanala i 2 dodatna IP kanala do rezolucije 6MP. Maksimalna rezolucija snimanja 4MP lite. Frame rate: 4 MP lite@15fps/ 1080p lite@25fps. Kompresija snimanja: H.265 Pro+. 1x VGA, 1x HDMI, 1x video out. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 1x USB 3.0. RS-485 komunikacija. 1HDD maksimalnog kapaciteta 10TB. Human/Vehicle Analysis na 4 kanala. Quick search by object or event type is supported.	call
iDS-7208HUHI-M2/S		5MP	Turbo AcuSense video snimač sa 8 analogna kanala i 4 dodatna IP kanala do rezolucije 8MP. Maksimalna rezolucija snimanja 8MP. Frame rate: 8 MP@8fps/ 5 MP@12fps/ 3K@12fps/ 4 MP@15fps/ 8 MP Lite@15fps/ 3 MP@18fps/ 1080p@25fps. Kompresija snimanja: H.265 Pro+. 1x VGA, 1x HDMI, 1x video out. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 1x USB 3.0. RS-485 komunikacija. 2HDD maksimalnog kapaciteta 10TB po disku. Human/Vehicle Analysis na 4 kanala. Quick search by object or event type is supported.	call
iDS-7208HTHI-M2/S(C)		4K ULTRA HD	Turbo HD video snimač sa 8 analogna kanala i 8 dodatnih IP kanala do rezolucije 8MP. Maksimalna rezolucija snimanja 8MP. Frame rate: 8 MP@15 fps/ 5 MP@20 fps/ 3K@20 fps/ 3 MP@18fps/ 4 MP@25fps/ 1080p@25 fps. Kompresija snimanja: H.265 Pro+. 1x VGA, 1x HDMI, 1x video out. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 1x USB 3.0. RS485 komunikacija. 2HDD maksimalnog kapaciteta 10TB po disku. Human/Vehicle Analysis na 4 kanala. Quick search by object or event type is supported. Line crossing and intrusion detection 8ch.	call
HD-TVI snimači 16ch				
iDS-7116HQHI-M1/S€			Turbo HD AcuSense video snimač sa 16 analogna kanala i 2 dodatna IP kanala rezolucije do 6MP. Maksimalna rezolucija snimanja 3K lite. Frame rate: 3k lite/5MP lite@12fps/4MP lite@15fps/1080p lite@25fps. Kompresija snimanja: H.265 Pro+. 1x VGA, 1x HDMI, 1x video out. 1x audio in, 1x audio out. 1x RJ45 10M/100M mrežni interfejs. 2x USB 2.0. 1HDD maksimalnog kapaciteta 10TB. Motion detection 2.0(Human/Vehicle Analysis), Facial Detection, Perimeter Protection (Human/Vehicle Analysis) do 4 kanala	call
iDS-7216HQHI-M1/XT		HIKVISION®	Turbo AcuSense video snimač sa 16 analogna kanala i 8 dodatna IP kanala do rezolucije 6MP. Maksimalna rezolucija snimanja 3K lite. Frame rate: 3K lite@12fps/1080p @15fps. Kompresija snimanja: H.265 Pro+. 1x VGA, 1x HDMI. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1xUSB 2.0, 2x USB 3.0. 1HDD maksimalnog kapaciteta 12TB.Human/Vehicle Analysis. Line Crossing Detection/ IntrusionDetection na 8 kanala.	call
iDS-7216HUHI-M2/X/4A+		HIKVISION® 4K ULTRA HD	Turbo HD AcuSense video snimač sa 16 analogna kanala i 16 dodatnih IP kanala do rezolucije 8MP. Maksimalna rezolucija snimanja 8MP. Frame rate:8 MP@8 fps/ 5MP@12fps/ 3K@12 fps/ 4 MP@15fps/ 3 MP@18fps/ 1080p@25fps. Kompresija snimanja: H.265 Pro+. 1x VGA, 1x HDMI, 1x video out. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 1x USB 2.0, 2x USB 3.0. RS485 komunikacija. 2HDD maksimalnog kapaciteta 12TB po disku. Motion Detection 2.0 (human/vehicle analysis). Perimeter Protection (human/vehicle analysis) na 8 kanala.	call
IP kamere i NVR				
Full Color IP - kolor slika i u potpunom mraku 24/7				
BMMBRL400WH		Longse Full Color	5MPix 1/2.8" SONY Starvis Back-illuminated CMOS sensor, Full Color IP bullet vodootporna kamera, mainstream rezolucije 2592*1944@25fp, 2560*1440@25fp, 1920*1080@25fps, objektiv 3,6mm, 0,01Lux, POE(802.3af), S/N ratio ≥52dB, 4 led diode warm white 4000K dometa do 25m, IP67, ONVIF, ROI, BLC, HDR 120dB, kompresija H.264 / H.264+ / H.265 / H.265+ / JPEG / AVI / MJPEG napajanje DC12V / 1000mA, dimenzije 268 x 95 x 88 mm, težina 1,5kg.	157
IP kamere 4K				
LVDHS800		Longse	4K Sony IMX274 + HI3519, IP dome vodootporna kamera, rezolucija 3840 x 2160 @ 30fps, kompresija H264/H265/JPEG/AVI, audio, objektiv 5mm, 0,01Lux, POE(802.3af), 18 IC dioda dometa do 20 m, IR-CUT, Defog, 3DNR, BLC, FLK, WDR, IP66, ONVIF 2.4, triple stream, IE8~11, napajanje 12V DC 850mA, dimenzije Φ139 x 122(H) mm, težina 800g.	309
IP kamere 5MPix				
AC-1455 INP		Longse	5MPix 1/2.8" SONY Starvis Back-illuminated CMOS sensor, IP dome vodootporna kamera, mainstream rezolucije 2592*1944 @ 25fp, 2560*1440 @ 25fp, 1920*1080 @ 25fps, 1280*720 @ 25fps, objektiv 2.8mm, 0,006Lux, NEMA POE, S/N ratio ≥60dB, 2 IC diode dometa do 25m, line cross, IP67, ONVIF, ROI, BLC, WDR 120dB, kompresija H.264 / H.264+ / H.265 / H.265+ / JPEG / AVI, napajanje DC12V / 850mA, dimenzije Ø108 x 85(H) mm, 0.4kg.	74

LIRDCA5XSS500		Longse	5MPix 1/2.8" SONY Starvis Back-illuminated CMOS sensor, IP dome vodootporna kamera, rezolucija 2592 x 1944 @ 20fps, motorizovani varifokalni objektiv 2.7-13.5mm , 0,01Lux, POE(802.3af) , 24 IC dioda dometa do 30m, kompresija H.264/H.264+ / H.265/H.265+ , IR-CUT, Defog, ROI, BLC, WDR, IP66, ONVIF 2.4, triple stream, IE8~11, napajanje 12V DC 950mA, dimenzije Φ 119 x 98(H) mm, težina 800g.	122
AC-4555 ISP			5MPix 1/2.8" SONY Starvis Back-illuminated CMOS sensor, IP bullet vodootporna kamera, mainstream rezolucije 2592*1944 @ 25fp, 2560*1440 @ 25fp, 1920*1080 @ 25fps, 1280*720 @ 25fps, interna memorija 4GB , objektiv 2.8mm, 0,01Lux, POE(802.3af) , S/N ratio $\geq$ 52dB, 2 IC diode dometa do 25m, IP67, ONVIF, ROI, BLC, HDR 120dB, kompresija H.264 / H.264+ / H.265 / H.265+ / JPEG / AVI / MJPEG napajanje napajanje DC12V / 700mA, dimenzije 171(W) x 73(H) mm, težina 0.75kg.	115
IP kamere 4MPix				
LIRDNTS400		Longse	4MPix OmniVision OV4689 + Hi3516D, IP dome vodootporna kamera, rezolucija 2560 x 1440 @ 20fps, kompresija H264/H265/JPEG/AVI , varifokalni objektiv 2.8-12mm, 0,01Lux, POE(802.3af) , 24 IC dioda dometa do 30 m, IR-CUT, Defog, 3DNR, BLC, FLK, WDR, IP66, ONVIF 2.4, triple stream, IE8~11, napajanje 12V DC 700mA, dimenzije Φ 131 x 93(H) mm, težina 800g.	110
IP kamere 2MPix				
LIRDQS200		Longse	2MPix Sony IMX323 + Hi3516CV200, IP dome vodootporna kamera, rezolucija 1920 x 1080 @ 25fps, kompresija H264/JPEG/AVI , objektiv 2.8-12mm , 0,01Lux, POE(802.3af) , slot za Micro SD karticu do 128GB, 24 IC dioda dometa do 30m, IR-CUT, Defog, 3DNR, BLC, FLK, WDR, IP66, ONVIF 2.4, triple stream, IE8~11, napajanje 12V DC 700mA, dimenzije Φ 120 x 104(H) mm.	95
HIKVISION IP				
Hikvision IP ColorVu				
DS-2CD1T47G2H-LIU		Longse	4MP mrežna Smart Hybrid Light kamera u bullet kućištu sa ColorVu tehnologijom. 1/3" CMOS sa progresivnim skeniranjem. Color: 0.001 Lux @ (F1.0, AGC ON), 0 Lux with Light. Maksimalna rezolucija 2560x1440. Fiksna optika 4 mm. Kompresija H.265+/H.265/H.264+/H.264. Nivo zaštite IP67. 120dB WDR. Domet IR/LED dioda 50 metara. Integriran mikrofoni. 12v napajanje, PoE. Odgovarajuća dozna je DS-1280ZJ-XS. Ugaoni nosač je DS-1276ZJ-SUS. Nosač za banderu DS-1275ZJ-SUS. Materijal: Metal i plastika.	163
DS-2CD1347G2H-LIU			4MP mrežna Smart Hybrid light kamera u turret kućištu sa ColorVu tehnologijom. 1/3" CMOS sa progresivnim skeniranjem. Color: 0.001 Lux @ (F1.0, AGC ON), 0 Lux with Light. Maksimalna rezolucija 2560x1440. Fiksna optika 2.8mm. Kompresija H.265+/H.265/H.264+/H.264. Nivo zaštite IP67. 120dB WDR. Domet IR/LED 30 metara. Integriran mikrofoni. 12v napajanje, PoE Odgovarajuća dozna je DS-1280ZJ-S. Nosač za banderu je DS-1275ZJSUS. Zidni nosač je DS-1272ZJ-110. Ugaoni nosač je DS-1276ZJ-SUS. Materijal: Metal i plastika.	148
IP kamere - HIKVISION				
DS-2CD2421G0-IW			2MP mrežna WiFi kamera u cube kućištu. 1/2.7 CMOS sa progresivnim skeniranjem. Color: 0.01 Lux @ (F1.6, AGC ON). Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Kompresija H.265+/H.265/H.264+/H.264. 120 dB WDR. Domet IC dioda do 10m. Integriran mikrofoni i zvučnik za dvosmernu audio komunikaciju. Slot za microSD karticu do 256GB. Video analitika: Line crossing, intrusion detection. 12V napajanje, PoE. Materijal: Plastika.	call
DS-2CD1121-I(2.8mm)(F)			2MP mrežna kamera u dome kućištu. 1/2.7" CMOS sa progresivnim skeniranjem. Color: 0.01Lux @ (F2.0, AGC ON). Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Kompresija H.264. Nivo zaštite IP67, IK10. DWDR. Domet IC dioda 30 metara. 12v napajanje, PoE. Odgovarajuća dozna je DS-1280ZJ-DM18. Nosač za banderu je DS-1275ZJ-SUS. Ugaoni nosač je DS-1267ZJSUS. Zidni nosač je DS-1272ZJ-110. Materijal: Metal i Plastika.	call
DS-2CD1123G2-LIU		HIKVISION®	2MP mrežna Smart Hybrid Light kamera u dome kućištu sa ColorVu tehnologijom. 1/2.9" CMOS sa progresivnim skeniranjem. Color: 0.005Lux @ (F1.6, AGC ON), B/W: 0 Lux sa IR. Maksimalna rezolucija 1920x1080. Fiksna optik 2.8mm. Kompresija H.265+/H.264+. Nivo zaštite IP67, IK08. DWDR. Domet LED/IR dioda 30 metara. Integriran mikrofoni. 12v napajanje, PoE. Odgovarajuća dozna je DS-1280ZJ-DM46. Nosač za banderu je DS-1275ZJ-SUS. Zidni nosač je DS-1272ZJ-120. Materijal: Metal i Plastika.	call
DS-2CD1143G2-LIU			4MP mrežna Smart Hybrid light kamera u turret kućištu sa ColorVu tehnologijom. 1/3" CMOS sa progresivnim skeniranjem. Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR. Maksimalna rezolucija 2560x1440. Fiksna optika 2.8mm. Kompresija H.265+/H.265/H.264+/H.264. Nivo zaštite IP67, IK08. 120dB WDR. Motion detection (human, vehicle). Integriran Mikrofoni. Domet IC dioda 30 metara. 12v napajanje, PoE. Odgovarajuća dozna je DS-1280ZJ-DM46. Nosač za banderu je DS-1275ZJ-SUS. Zidni nosač je DS-1272ZJ-120. Materijal: Metal i Plastika.	call

DS-2CD1127G2-LUF (2.8mm)		2MP mrežna kamera u dome kućištu sa ColorVu tehnologijom. 1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.001Lux @(F1.0,AGC ON), B/W: 0 Lux sa IR. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Kompresija H.265 /H.264+. Nivo zaštite IP67, IK08. DWDR. Domet LED dioda 30 metara. Integriran mikrofoni. Slot za microSD karticu do 256GB. 12v napajanje,PoE. Odgovarajuća dozna je DS-1280ZJ-DM46. Nosač za banderu je DS-1275ZJ-SUS. Zidni nosač je DS-1272ZJ-120. Materijal: Metal i Plastika.	call
DS-2CD1321-I (2.8mm)(F)		2MP mrežna kamera u turret kućištu. 1/2.7" CMOS sa progresivnim skeniranjem. Color: 0.01 Lux @(F2.0, AGC ON). Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Kompresija H.264. Nivo zaštite IP67. DWDR. Domet IC dioda 30 metara. 12v napajanje,PoE. Odgovarajuća dozna je DS-1280ZJ-S. Zidni nosač je DS-1272ZJ-110-TRS. Ugaoni nosač je DS-1276ZJ-SUS. Nosač za banderu je DS-1275ZJ-SUS. Materijal: Metal i Plastika.	call
DS-2CD2123G2-LIS2U (2.8mm)		2MP mrežna AcuSense Smart Hybrid Light kamera u dome kućištu. 1/2.7" CMOS sa progresivnim skeniranjem. Color: 0.005Lux @(F1.6,AGC ON), B/W: 0 Lux sa IR. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. Nivo zaštite IP67, IK10. 120 dB WDR. Domet LED/IR dioda 30 metara. Slot za microSD karticu do 512GB. 1x alarm in, 1x alarm out. Integriran mikrofoni. Video analitika: Line crossing detection, intrusion detection, region entrance/region exiting supports human and vehicle targets classification. 12v napajanje,PoE. Odgovarajuća dozna je DS-1280ZJ-DM46. Nosač za banderu je DS-1275ZJ-SUS. Zidni nosač je DS-1272ZJ-120. Materijal: Meta	call
DS-2CD1343G2-LIU (2.8mm)		4MP mrežna Smart Hybrid light kamera u turret kućištu. 1/3" CMOS sa progresivnim skeniranjem. Color: 0.005 Lux @ (F1.6, AGC ON). Maksimalna rezolucija 2560x1440. Fiksna optika 2.8mm. Kompresija H.265+/H.264+. Nivo zaštite IP67. WDR 120dB. Integriran mikrofoni. Domet IR/LED 30 metara. Analitika: Motion Detekction (Raspoznavanje ljudi i vozila). Napajanje 12VDC, PoE. Odgovarajuća dozna je DS-1280ZJ-S. Nosač za banderu je DS-1275ZJ-SUS. Zidni nosač je DS-1272ZJ-110-TRS. Ugaoni nosač je DS-1276ZJ-SUS. Materijal: Metal i Plastika.	call
DS-2CD2143G2-I		4MP mrežna kamera u dome kućištu sa AcuSense tehnologijom. 1/3" CMOS sa progresivnim skeniranjem. Color: 0.005 Lux @ (F1.6, AGC ON), 0 Lux with IR on. Maksimalna rezolucija 2688x1520. Fiksna optika 2.8 mm. Kompresija H.265+/H.265/H.264+/H.264. Nivo zaštite IP67, IK10. 120dB WDR. Domet IC dioda 30 metara. Slot za microSD karticu do 256GB. Video analitika: Line crossing detection, intrusion detection, Face Detection. 12v napajanje, PoE. Odgovarajuća dozna je DS-1280ZJ-DM18. Nosač za banderu je DS-1275ZJ-SUS. Ugaoni nosač je DS-1276ZJ-SUS. Zidni nosač je DS-1272ZJ-110. Materijal: Metal i Plastika.	call
DS-2CD1743G2-LIZU		4MP mrežna Smart Hybrid light kamera u turret kućištu. 1/3" CMOS sa progresivnim skeniranjem. Color: 0.005 Lux @(F1.6, AGC ON), B/W: 0 Lux with IR. Maksimalna rezolucija 2560x1440. Varifokalna optika 2.8 - 12mm. Kompresija H.265+/H.265/H.264+/H.264. Nivo zaštite IP67, IK08. 120dB WDR. Motion detection (human,vehicle). Integriran Mikrofoni. Domet IC dioda 30 metara. Slot za microSD karticu do 512GB. 12v napajanje,PoE. Odgovarajuća dozna je DS-1280ZJ-DM46, DS-2280ZJ-WA120. Nosač za banderu je DS-1275ZJSUS. Zidni nosač je DS-1272ZJ-120. Materijal: Metal i Plastika.	call
DS-1280ZJ-DM18		Aluminijumska razvodna kutija, dimenzije Φ111mm, težina 150g	call
DS-1280ZJ-DM21		Razvodna kutija za smeštanje kablova i napajanja. Vodootporni dizajn, dimenzije Φ137×42mm, težina 250g	call
DS-2CD1021-I (2.8mm)(F)		2MP mrežna kamera u bullet kućištu. 1/2.7 CMOS sa progresivnim skeniranjem. Color: 0.01Lux @(F2.0, AGC ON). Maksimalna rezolucija 1920x1080. Fiksna optika 2.8 mm. Kompresija H.264+/H.264. Nivo zaštite IP67. DWDR. Domet IC dioda do 30m. 12V napajanje, PoE. Odgovarajuća dozna je DS-1280ZJ-XS. Materijal: Metal i Plastika.	call
DS-2CD1043G2-LIU (2.8mm)		4MP mrežna Smart Hybrid Light kamera u bullet kućištu. 1/3" CMOS sa progresivnim skeniranjem.Color: 0.005 Lux @ (F1.6, AGC ON). Maksimalna rezolucija 2560x1440. Fiksna optika 2.8 mm. Kompresija H.265+/H.264+. Nivo zaštite IP67. WDR 120dB. Domet IC/LED dioda 30 metara. Integriran mikrofoni. Analitika: Motion Detection (Raspoznavanje ljudi i vozila). Napajanje 12VDC, PoE. Odgovarajuća dozna je DS-1280ZJ-XS. Materijal: Metal i Plastika.	call
DS-2CD2043G2-I		4MP mrežna kamera u bullet kućištu sa AcuSense tehnologijom. 1/3" CMOS sa progresivnim skeniranjem.Color: 0.005 Lux @ (F1.6, AGC ON), 0 Lux with IR on. Maksimalna rezolucija 2688x1520. Fiksna optika 2.8 mm. Kompresija H.265+/H.265/H.264+/H.264. Nivo zaštite IP67. 120dB WDR. Domet IC dioda 40 metara. Slot za microSD karticu do 256GB. Video analitika:Line crossing detection, intrusion detection, region entrance detection, region exiting detection, Scene change detection, Face Capture. 12v napajanje,PoE. Odgovarajuća dozna je DS-1280ZJ-XS. Materijal: Metal.	call

DS-2CD2083G0-I 	8MP mrežna kamera u bullet kućištu. 1/2.5" CMOS sa progresivnim skeniranjem. Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR. Maksimalna rezolucija 3840x2160. Fiksna optika 4 mm. Kompresija H.265+/H.265/H.264+/H.264. Nivo zaštite IP67. 120dB WDR. Domet IC dioda 30 metara. Slot za microSD karticu do 128GB. Video analitika: Line crossing detection, intrusion detection, face detection. 12v napajanje,PoE. call
DS-2CD2T43G2-4LI2U (4mm) 	4MP mrežna Smart Hybrid Light kamera u bullet kućištu sa AcuSense tehnologijom. 1/2.9" CMOS sa progresivnim skeniranjem. Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with light. Maksimalna rezolucija 2688x1520. Fiksna optika 4mm. Kompresija H.265+/H.265/H.264+/H.264. Nivo zaštite IP67, IK10. 120dB WDR. Domet LED/IR dioda 80 metara. Slot za microSD karticu do 512GB. Integriran mikrofoni. Video analitika: Line crossing detection, intrusion detection (human and vehicle). 12v napajanje,PoE. Odgovarajuća dozna je DS-1260ZJ. Nosač za banderu je DS-1275ZJ-S-SUS,DS-1275ZJ-SUS. Ugaoni nosač DS-1276ZJ-SUS. Materijal: Metal. call
DS-2CD2T83G2-4I  	8MP mrežna kamera u bullet kućištu sa AcuSense tehnologijom. 1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR. Maksimalna rezolucija 3840x2160. Fiksna optika 2.8mm. Kompresija H.265+/H.265/H.264+/H.264. Nivo zaštite IP67. 120dB WDR. Domet IR dioda 80 metara. Slot za microSD karticu do 256GB. Video analitika: Line crossing detection, intrusion detection, region entrance detection, region exiting detection, Face Capture. 12v napajanje,PoE. Nosač za banderu je DS-1275ZJ. Odgovarajuća dozna je DS-1260ZJ. Ugaoni nosač je DS-1276ZJ-SUS. Materijal: Metal i Plastika. call
DS-2CD1643G2-LIZU 	4MP mrežna Smart Hybrid Light kamera u bullet kućištu. 1/3" CMOS sa progresivnim skeniranjem. Color: 0.005 Lux @ (F1.6, AGC ON), 0 Lux with IR. Maksimalna rezolucija 2560x1440. Varifokalna optika 2.8 - 12 mm. Kompresija H.265+/H.265/H.264+/H.264. Nivo zaštite IP67. 120dB WDR. Domet IR/LED dioda 50 metara. Integriran mikrofoni. Slot za microSD karticu do 512GB. 12v napajanje,PoE. Odgovarajuća dozna je DS-1280ZJ-S, DS-1260ZJ. Ugaoni nosač je DS-1276ZJ-SUS. Nosač za banderu DS-1275ZJ-SUS. Materijal: Metal i plastika. call
DS-2CD2643G2-IZS 	4MP mrežna kamera u bullet kućištu sa AcuSense tehnologijom. 1/3" CMOS sa progresivnim skeniranjem. Color: 0.005 Lux @ (F1.6, AGC ON), 0 Lux with IR on. Maksimalna rezolucija 2688x1520. Varifokalna optika 2.8 - 12 mm. Kompresija H.265+/H.265/H.264+/H.264. Nivo zaštite IP67, IK10. 120dB WDR. Domet IC dioda 60 metara. 1x alarm in, 1x alarm out. 1x audio in, 1x audio out. Slot za microSD karticu do 256GB. Video analitika: Line crossing detection, intrusion detection, Face Detection. 12v napajanje,PoE. Nosač za banderu je DS-1275ZJ-S-SUS. Odgovarajuća dozna je DS-1276ZJ. Ugaoni nosač je DS-1276ZJ-SUS. Materijal: Metal. call
Kamere za prepoznavanje tablica - HIKVISION	
iDS-2CD7A46G0/P-IZHSY  	4MP mrežna ANPR kamera u bullet kućištu sa DarkFighter tehnologijom. 1/1.8 CMOS senzor sa progresivnim skeniranjem. Color: 0.0005 Lux @ (F1.2, AGC ON), B/W: 0.0001 Lux @ (F1.2, AGC ON) 0 Lux with IR. Maksimalne rezolucije 2688x1520. Varifokalna optika 2.8 - 12mm. Kompresija H.265+/H.265/H.264+. Nivo zaštite IP67, IK10. 140dB WDR. Domet IC dioda 50 metara. 2x alarm in, 2x alarm out. 1x audio in, 1x audio out. Slot za microSD karticu do 256GB. Video analitika: Intrusion detection, scene change detection, audio exception detection, defocus detection, Line crossing, Region entrance, region exiting detection. Road Traffic and Vehicle Detection. Napajanje 12v,PoE. Nosač za banderu je DS-1275ZJ-SUS. Ugaoni nosač je DS-1476ZJ-Y. Materijal: Metal. call
NVR - HIKVISION	
DS-7604NXI-K1 	Mrežni video snimač za 4 kanala sa AcuSense tehnologijom. Maksimalna rezolucija snimanja 12MP. Bandwidth In 40Mbps, Bandwidth 80Mbps. Kompresija snimanja H.265+, H.265. 1 x HDMI izlaz, 1 x VGA izlaz. 1x audio in, 1x audio out. 1x RJ45 10M/100M/1000M mrežni interfejs. 2x USB 2.0. Mogućnost priključenja 1HDD maksimalnog kapaciteta 10TB. Motion Detection 2.0, Human and Vehicle Analysis. Facial detection and analytics. call
DS-7608NXI-K2 	Mrežni video snimač za 8 kanala sa AcuSense tehnologijom. Maksimalna rezolucija snimanja 12MP. Bandwidth In 80Mbps. Bandwidth Out 160Mbps. Kompresija snimanja H.265+, H.265, H.264+, H.264. 1xHDMI izlaz, 1x VGA izlaz, 1x audio in, 1x audio out, 4x Alarm In, 1x Alarm Out. 1x RJ45 10M/100M/1000M mrežni interfejs. 2x USB2.0. 2HDD maksimalnog kapaciteta do 10TB po disku. Svi kanali podžavaju Motion Detection 2.0, human and Vehicle Analysis. Facial detection and analytics. Human and Vehicle Analysis 8-ch (1-ch human face capture, 4-ch face picture comparison alarm). call

DS-7616NXI-K2			Mrežni video snimač za 16 kanala. Maksimalna rezolucija snimanja 12MP. Bandwidth In 160Mbps. Bandwidth Out 160Mbps. Kompresija snimanja H.265+, H.265, H.264+, H.264. 1x HDMI izlaz,1 x VGA izlaz. 1x audio in, 1x audio out. 4x Alarm In, 1x Alarm Out. 2x RJ45 10M/100M/1000M mrežni interfejs. 2xUSB2.0. 2HDD maksimalnog kapaciteta do 10TB po disku.Human and Vehicle Analysis. Facial detection and analytics. Human and Vehicle nalysis 16-ch (1-ch human face capture, 4-ch face picture comparison alarm).	call
HIKVISION®				
DS-7632NXI-K2			Mrežni video snimač za 32 kanala sa AcuSense tehnologijom. Maksimalna rezolucija snimanja 12MP. Bandwidth In 256Mbps. Bandwidth Out 160Mbps. Kompresija snimanja H.265+, H.265, H.264+, H.264. 1x HDMI izlaz,1 x VGA izlaz. 1x audio in, 1x audio out. 4x alarm in, 1x alarm out. 1x RJ45 10M/100M/1000M mrežni interfejs. 2xUSB2.0. 2HDD maksimalnog kapaciteta do 10TB po disku. Human and Vehicle Analysis. Facial detection and analytics. Human and Vehicle Analysis 32-ch (1-ch human face capture, 4-ch face picture comparison alarm).	call
IP - PTZ kamere				
DS-2DE3A400BW-DE(F1)(T5)			4MP mrežna kamera u PTZ kućištu sa AcuSense tehnologijom. 1/1.8" CMOS sa progresivnim skeniranjem. Color: 0.0005Lux @ (F1.0, AGC ON), 0 Lux with white light. Maksimalna rezolucija 2560x1440.Fiksna optika 4 mm. Kompresija H.265+ /H.265 /H.264+ /H.264. Nivo zaštite IP66. 120dB WDR. Domet LED dioda 30 metara. 1x alarm in, 1x alarm out. 1x audio in, 1x audio out, Integrisan zvučnik i mikrofoni. Slot za microSD karticu do 512GB. Video analitika: Face Capture , Intrusion Detection, Line Crossing Detection, Region Entrance Detection, Region Exiting Detection. 12V napajanje,PoE.	call
DS-2DE7A425IW-AEB(T5)		HIKVISION®	4mp mrežna kamera u PTZ kućištu sa DarkFighter tehnologijom. 1/2.8" CMOS sa progresivnim skeniranjem. Color: 0.005 Lux @ (F1.5, AGC ON), B/W: 0.001 Lux@(F1.5, AGC ON). Maksimalna rezolucija 2560 × 1440. Varifokal 4.8 - 120 mm. H.264, H.265, H.265+. Zaštita IP66, IK10. WDR 120dB. Domet IC diode 200m. 2x alarm in, 1x alarm out. 1x audio out, 1x audio in, integrisan zvučnik. Slot za microSD karticu do 256GB. Video analitika: Line crossing detection, intrusion detection, region entrance detection, region exiting detection, unattended baggage detection, object removal detection, audio exception detection. Napajanje 24VAC, Hi-PoE. Zidni nosač DS-1604ZJ. Nosač za banderu DS-1673ZJ. Materijal: Metal.	call
DS-1602ZJ			Aluminijumski nosač za kamere. Kanal za prolazak kablova i sigurnosno uže, dimenzije 97x182x305mm, težina 1050g	call
DS-1602ZJ-Pole			Vertikalni nosač za Speed Dome kamere. Aluminijumski nosač sa doznom za ptz kamere. Materijal aluminijum i čelik. Dimenzije 117mm x 194mm x 451.3mm. Težina 2 kg.	call
DS-1602ZJ-Corner			Zidni nosač za montiranje u ćošak Malih dimenzija, sigurnosno uže, dimenzije 176.8×194×417.8mm, težina 2809g	call
Monitori i interaktivni tableti				
DS-D5024FN			23.8 inča monitor u FHD rezoluciji. LED Monitor predviđen da radi 24/7 za nadgledanje video nadzora.Rezolucija1920x1080 @60Hz.Brightness 250cd/m². Contrast Ratio 4000:1. 1x HDMI input, 1 x VGA input.	call
DS-D5B65RB/A		HIKVISION®	Interaktivni 4K touch screen ekran. Veličina ekrana 65 inča. Rezolucija 3840x2160 @ 60Hz, pozadinsko osvetljenje tipa DLED. Osvetljenjes 350 cd/m². kontrast 1200:1, Pixel pitch 0.124(H) x 0.372 (V)mm, ugao gledanja 178°(H)/178°(V). Operativni sistem Android, procesor 4-core A73 × 2 + A53 × 2, 1.5 GHz. 2x HDMI (max 4K @ 60Hz), 1 x HDMI out. 2 zvučnika 16W. 2 Mrežna interfejsa i Bluetooth 5.0. 2x USB 2.0. Radna temperatura 0 do 40 C. Potrošnja 250W.	call
DS-D5ABKY2-S			Mobilni stojeći nosač za interaktivne ekrane od 55 do 75 inča. SPCC visokokvalitetna čelična ploča, sive boje. Dimenzije: 1.160mm x 688mm x 1.560mm. Težina 20kg. Nosivost do 85kg.	call
HDD				
HDD-1T		WD PURPLE HDD, 1TB	Upit	
HDD-2T		WD PURPLE HDD, 2TB	Upit	
HDD-4T		WD PURPLE HDD, 4TB	Upit	
Memorijske kartice				
WD Purple SC QD102 64GB			MicroSD kartica kapaciteta 64GB SDA 6.0, 3D NAND tehnologija, radna temperatura - 25 C° to 85C°, Speed Class 10 UHS Speed Class 1 (U1), Write/Read 60/100 MB/s	32.4

WD Purple SC QD102 128GB		MicroSD kartica kapaciteta 128GB High Endurance CCTV SDA 6.0, 3D NAND tehnologija, radna temperatura -25 C° to 85C°, Speed Class 10 UHS Speed Class 1 (U1), Write/Read 60/100 MB/s	47
WD Purple SC QD102 256GB		MicroSD kartica kapaciteta 256GB Ultra Endurance CCTV SDA 6.0, 3D NAND tehnologija, radna temperatura -25 C° to 85C°, Speed Class 10 UHS Speed Class 1 (U1), Write/Read 60/100MB/s	119
Video baluni			
CF-201		Pasivni video Balun za prenos video signala putem UTP CAT5/5E/6 kablja, kompatibilan sa AHD / TVI / CVI / CVBS, maksimalna dužina do 400m za AHD/CVI odnosno 300m za TVI/CVBS, podržane rezolucije 720P / 960P / 1080P / 3MP / 4MP / 5MP / 8MP. Cena je za par.	7.5
DS-1H18S/E©		Hikvision videobalun podržava kamere do 8mp. Prenos signala do 250m. Kategorije 5e,6. HDCVI/TVI/AHD/CVBS. Radna temperatura od -10 do 70 stepeni. Cena je za par.	8.4
NT-621A / (STK 213B+)		Pasivni video Balun za prenos audio/video signala i napajanja putem UTP kablja, maksimalna dužina kablja do 100 metara. Cena za par.	6.5
STK204LL		4-kanalni pasivni video balun za prenos video signala putem UTP kablja, lak za montažu, ulazni konektor RJ 45, mogućnost montaže na zid	11
NT-2401 T		Aktivni transmiter za prenos jednog video signala putem UTP kablja. Max domet 2400 metara. 12 V DC .	16
NT-2401 R		Aktivni risiver za prijem jednog video signala putem UTP kablja 12 V DC .	19
NT-2504 R		Aktivni risiver za prijem 4 video signala putem UTP kablja.	60
Nosači i kućišta			
SAB-01B		Pokretni plastični nosač kamera u crnoj boji, dužina 130mm.	1
SAB-07		Pokretni metalni nosač za YC seriju kamera.	1
SAB-06-B		Pokretni metalni nosač dužine 170 mm.	1
EJWM 100		Metalni nosač za dome antivandal kamere	11
GL 610		Kućišta za unutrašnje / spoljasnje za montažu u spuštenu plafon, dimenzije 125(W) x 100(H) x 335(L)mm.	8.0
GL 208		Nosač za kućište GL619 sa skrivenom kabložom.	11
Napajanja			
HTD-CVT1202000		Pretvarač 24VAC-12VDC, ulazni napon AC 20~24V, izlazni napon : 12V DC / 2A, dimenzije 61.5*33*24.5mm, težina 46.6gr.	8
HT1000		Adapter (switch) Ulaz : 100~240V AC Izlaz : 12V DC / 1A, dimenzije 96*47*30, težina 115gr.	6
HT2000		Adapter (switch) Ulaz : 100~240V AC Izlaz : 12V DC / 2A, dimenzije 96*47*30, težina 130gr.	7.5
HT2000V		Adapter (switch) Ulaz : 100~240V AC Izlaz : 12V DC / 2A, dimenzije 83*43*68, težina 110gr.	7.5
HT2000WP		Adapter (switch) za montažu u doznu Ulaz : 100~240V AC Izlaz : 12V DC / 2A, dimenzije 51.5*41.5*21, težina 150gr. Vodootporno IP67.	10.5
HT24W		BOX napajanje za kamere, ulaz: 100~240V AC, Izlaz: 12~13V DC / 2A. Regulacija izlaznog napona. Dimenzije 85*58*34mm, težina 130gr.	11
HT2000-W		Adapter (switch) za spoljnu montažu, ulaz: 100~240V AC Izlaz: 12V DC / 2A, dimenzije 84.8*42*136.5mm, težina 170.9gr, radna temperatura -20~60C.	10
HT3000		Adapter (switch) Ulaz : 100~240V AC Izlaz : 12V DC / 3A, dimenzije 125*50*30, težina 250gr.	11
HT3000V		Adapter (switch) Ulaz : 100~240V AC Izlaz : 12V DC / 3A, dimenzije 85*46*68, težina 250gr.	10
HT5000		Adapter (switch) Ulaz : 100~240V AC Izlaz : 12V DC / 5A, dimenzije 119.4*53*39, težina 372gr.	16

HT1205000-4		Cetvorokanalni adapter za napajanje, ulaz: AC 100~240V, izlaz: 11,8~15V DC / 5A. Regulacija izlaznog napona. Dimenzije 138.6*54.8*37mm, težina 404gr.	19
HT60W		BOX napajanje za kamere, ulaz: 100~220V AC, Izlaz: 11,8~14V DC / 5A. Regulacija izlaznog napona. Dimenzije 159.5*98*41.9mm, težina 407gr.	21
HT120W		BOX napajanje za kamere, ulaz: 100~220V AC, Izlaz: 11~16V DC / 10A. Regulacija izlaznog napona. Dimenzije 159.5*98*41.9mm, težina 407gr.	24
HTD120W		BOX napajanje za kamere, ulaz: 100~220V AC, Izlaz: 11~15V DC / 10A. Regulacija izlaznog napona, ventilator za hlađenje. Dimenzije 159.5*98*41.9mm, težina 488gr.	29
HTD120W-B		BOX napajanje za kamere, ulaz: 100~220V AC, Izlaz: 12~14V DC / 10A. Regulacija izlaznog napona u opsegu od 12 do 15V. Mogućnost priključenja backup baterije. Dimenzije 158*99*43mm, težina 430gr.	45
CP1204-3A-B		Cetvorokanalno BOX napajanje za kamere, moгуce dodavanje back-up akumulatora 12V 7Ah , ulaz: 90~220V AC, Izlaz: DC12V+/-5% DC / 3A , dimenzije 265x205x90mm, težina 1,9kg. Isporucuje se bez akumulatora.	47
HT1218-10A		Osamnaestokanalno BOX napajanje za kamere, ulaz: 100~220V AC, Izlaz: 12~14V DC / 10A, max 1.1A po kanalu. Regulacija izlaznog napona u opsegu od 12 do 16V. Dimenzije 246*208*52mm, težina 1.61 Kg.	56
HT1218-20A-B		Osamnaestokanalno BOX napajanje za kamere, ulaz: 100~220V AC, Izlaz: 11~15V DC / 20A, max 2A po kanalu. Mogućnost priključenja backup baterije 12V 7Ah , regulacija izlaznog napona, ventilator za hlađenje. Dimenzije 264*206*90mm, težina 2.49 Kg.	99
HTD1217-10A-B		Sedamnaestokanalno rack mount napajanje sa displejem za prikaz radnog napona i potrošnje struje u realnom vremenu, ulaz: 100~220V AC, Izlaz: 11~15V DC / 10A, max 2A po kanalu za kanale 1~16 i 4A za kanal 17, regulacija izlaznog napona, mogućnost priključenja back-up baterije. Dimenzije 485.4 * 230 * 65.6mm (1.5U/19"), težina 2.9 Kg.	140
Mikrofoni			
AM-003		Visoko kvalitetni mikrofonski modul sa pojačavačem, napajanje 4-14 V, potrošnja 10 mA, pokriva do 50 kvm.	5
JR-501C-1		Napajanje 6-12V, potrošnja 12 mA, Izlazna impedansa 600Ω, frekventni opseg 200Hz ~ 20KHz, izlazni nivo 0~6V, pokriva do 50 kvm, kabl sa konektorima.	7
JR-502B		Visoko kvalitetni mikrofonski modul sa pojačavačem, kabl bez konektora, podešavanje osetljivosti, napajanje 6-14V, potrošnja 0.5~60 mA, Izlazna impedansa 600Ω, frekventni opseg 100Hz~6KHz, izlazni nivo 0~6V, pokriva do 100 kvm. Dimenzije 39.5 x 31 x 16 mm.	9
JR-2009		Visoko kvalitetni mikrofonski modul sa pojačavačem, podešavanje osetljivosti, napajanje 6-14V, potrošnja 0.5~60 mA, Izlazna impedansa 600Ω, fre. opseg 100Hz~6000Hz, izlazni nivo 0~6V, pokriva do 100 kvm. Dimenzije 40(H)x 69(Φ)	10
Aktivna mrežna oprema			
LS-HT412		Longse 4-portni PoE Switch, IEEE 802.3af Power over Ethernet (PoE) standard; 4 x 10/100Mbps RJ45 PoE Porta (Port 1 ~ 4) + 2 UpLink x 10/100Mbps (Port 5 ~ 6), PoE Power Budget max 60W. Dimenzije 220mm x 140mm x 40mm.	64
DS-3E0106P-E/M		HIKVISION 4-portni (4+2) neupravljivi megabitni PoE svič. 2 megabitni Hi-PoE port, 2 megabitna PoE porta, 2 megabitna Ethernet porta. PoE power budget 35W, 30W po portu. Metalno kućište, bez ventilatora. Operativna radna temperatura -10 ~ 40C. Napajanje 48VDC, 0.8A. Zaštita od prenapona 6KV za PoE portove.	57
LS-HT812		Longse 8-portni PoE Switch, IEEE 802.3af Power over Ethernet (PoE) standard; 8 x 10/100Mbps RJ45 PoE Porta (Port 1 ~ 8) + 2 x UpLink x 10/100/1000Mbps (Port 9 ~ 10), PoE Power Budget max 100W. Dimenzije 220mm * 140mm * 40mm.	105
DS-3E0109P-E/M(B)		HIKVISION 8-portni (8+1) neupravljivi megabitni PoE svič. 8 megabitna PoE porta, 1 megabitni Ethernet port. PoE power budget 60W, 30W po portu. Metalno kućište, bez ventilatora. Operativna radna temperatura -10 ~ 55C. Napajanje 48VDC, 1.35A. Zaštita od prenapona 6KV za PoE portove.	72
DS-3E0310HP-E		8-portni (8+2) neupravljivi megabitni PoE svič. 1 megabitni Hi-PoE port, 7 megabitna PoE porta, 2 gigabitna Ethernet porta. PoE power budget 110W, 90W na prvom portu, od 2 do 8 porta 30W po portu. Metalno kućište, bez ventilatora. Operativna radna temperatura -10 ~ 55C. Napajanje 48VDC, 2.5A. Zaštita od prenapona 6KV za PoE portove.	178
LS-HT1612		Longse 16-portni PoE Switch, IEEE802.3af, IEEE802.3at, Power over Ethernet (PoE) standard; 16 x 10/100Mbps RJ45 PoE Porta (Port 1 ~ 16) + 2 x UpLink x 10/100/1000Mbps (Port 17 ~ 18), PoE Power Budget max 240W. Dimenzije 290mm * 200mm * 44mm.	200

Pasivna mrežna oprema			
WS-6406A		Rek orman za zidnu montažu, 6U, 600x450x368 u kompletu sa šrafovim i maticama za postavljanje opreme, vrata sa bravicom i ključem, vrata se otvaraju do 180 stepeni, leva i desna strana se mogu skidati, otvori za prolaz kablova, na gornjoj strani se nalaze ležišta za dva 12cm ventilatora, dostupan u sivoj boji, maksimalna nosivost 60Kg, IP20	89
WS-6409A		Rek orman za zidnu montažu, 9U, 600x450x501 u kompletu sa šrafovim i maticama za postavljanje opreme, vrata sa bravicom i ključem, vrata se otvaraju do 180 stepeni, leva i desna strana se mogu skidati, otvori za prolaz kablova, na gornjoj strani se nalaze ležišta za dva 12cm ventilatora, dostupan u sivoj boji, maksimalna nosivost 80Kg, IP20	104
DN-91410		Modularni patch panel 24p, Prazan, Sivi, 1U, za rek 19" Za kategoriju 6, koristi se sa KJ 93601, KJ 93603, KJ 93606 i KJ 93615	19.8
DN-93615		Sertifikovan konektor za SFTP kabl kategorije 6 (CAT6a)	4
WS-S 1U 450		Fiksna polica, 1U (sa ušicama za kačenje na prednje raster letve) nosivost do 20Kg, dubina 250mm, za rekove dubine 450mm i 600mm, dostupna u sivoj boji	17.4
Elco SL 8M 1U		Razvodni panel 19" 220V, 8 utičnih mesta sa prekidačem Dužina napojnog kabla 2m, u crno/sivoj boji	27.5
CCTV testeri			
Tester X7MOVTDHS		CCTV tester + digitaln multimeter + optical power meter + visual fault locator, kompatibilan sa AHD / CVI / TVI / CVBS / HD-SDI i IP kamerama do rezolucije 4K (8MPix), H264&H265, Retina touch screen displej 7" rezolucije 1920 x 1200, Wi-Fi, LAN 10/100/1000 Mbps, HDMI izlaz / HDMI ulaz 4K, RJ45 TDR cable tester, RAPID onvif, POE tester, instalirane aplikacije: iVMS-4500HD, XMeye, gDMSS, EZView... izlaz DC12V 3A / DC24V 2A, Li-ion Polymer baterija 7800mAh, dimenzije 240 mm x 154mm x 46mm, težina 0.980gr.	639 FIX

Sve cene su iskazane u EUR sa obračunatim PDV-om, podložne su promenama i zavisne od odnosa DIN/EUR/USD.

Plaćanje se vrši u dinarima po važećem prodajnom kursu poslovne banke.

AMS electronic d.o.o. zadržava pravo izmene cena bez prethodne najave.

Dostupna i oprema koje nema u cenovniku - pozovite radi dogovora !

Za detaljnije informacije, molimo kontaktirajte našu službu prodaje ili posetite www.amselectronic.com