





AHD kamere i snimači

Full Color - kolor slika i u potpunom mraku 24/7





















FC-5350		<p>1/2.8" SONY Starvis Back-illuminated CMOS sensor, kolor slika i u potpunom mraku 24/7, vodootporna kamera rezolucije 5 megapiksela, AHD/TVI: 5M @ 12.5fps, 4M @ 25fps, 2M @ 25fps, 720P @25fps; CVI: 4M / 2M / 720p @ 25fps, CVBS 25fps, 0,005Lux, objektiv 3,6mm ili 6mm, IR-CUT, IP67, WDR, AI-DNR, Starlight, UTC, 4 led diode warm white 4000K dometa do 40m, nosač sa skrivenom kablazom, napajanje DC12V / 750mA, dimenzije 268(W) x 95(H) x 88(D) mm, težina 1,5kg.</p>	83
---------	---	--	----


AHD kamere 4 Mpix

LBP90AD400V		<p>1/3" OmniVision OV4689 CMOS Sensor, AHD vodootporna kamera rezolucije 4 megapiksela, 0,01 Lux / F1.2, varifokalni objektiv 2.8-12 mm, IR-CUT, IP66, WDR, 3DNR, UTC, OSD, 6 IC diode dometa do 60m, nosač sa skrivenom kablazom, napajanje DC12V / 1000mA, dimenzije 211(W) * 92(H) * 90(D)mm., težina 1400g.</p>	109
LBW30AD400V		<p>1/3" OmniVision OV4689 CMOS Sensor, AHD vodootporna kamera rezolucije 4 megapiksela, 0,01 Lux / F1.2, megapikselsni objektiv 2.8 mm, IR-CUT, IP66, WDR, 3DNR, UTC, OSD, 2 IC diode dometa do 30m, nosač sa skrivenom kablazom, napajanje DC12V / 700mA, dimenzije 162(W) * 88(H) * 86(D)mm., težina 600g.</p>	75
LIRDCAD400V		<p>1/3" OmniVision OV4689 CMOS Sensor, AHD vodootporna kamera rezolucije 4 megapiksela, 0,01 Lux / F1.2, varifokalni objektiv 2.8-12 mm, IR-CUT, IP66, WDR, 3DNR, UTC, OSD, 24 IC dioda dometa do 30m, napajanje DC12V / 700mA, dimenzije 93(H) x 131(Φ)mm, težina 800g.</p>	85

AHD kamere 5 Mpix

Kućište kamere B220A		<p>Duboka metalna osnova za dome kamere sa fiksnom optikom Ø 9,3cm dubine 4cm za smestaj video baluna, konektora, napajanja ...</p>	9
AC-3150S		<p>1/2.8" SONY Starvis Back-illuminated CMOS sensor, AHD / TVI / CVI / CVBS vodootporna kamera rezolucije 5 megapiksela, AHD: 5M@20fps/12.5fps, 4M/2M@25fps, TVI: 5M@20fps/12.5fps, 4M/2M@25fps, CVI: 5M@20fps, 4M/2M@25fps, varifokalni objektiv 2.8-12mm, IR-CUT, IP67, WDR, 3DNR, UTC, OSD, 24 IC dioda dometa do 30m, napajanje DC12V / 750mA, dimenzije Φ120 x 98(H) mm, težina 800g</p>	89
Kućište kamere B170		<p>Duboka metalna osnova za dome kamere sa varifokalnom optikom Ø 12cm dubine 4cm za smestaj video baluna, konektora, napajanja ...</p>	11
LIN60HTC500ESL		<p>1/2.8" SONY Starvis Back-illuminated CMOS sensor, AHD / TVI / CVI / CVBS vodootporna kamera rezolucije 5 megapiksela, AHD: 5M@20fps/12.5fps, 4M/2M@25fps, TVI: 5M@20fps/12.5fps, 4M/2M@25fps, CVI: 5M@20fps, 4M/2M@25fps, varifokalni objektiv 2.8-12 mm, IR-CUT, IP67, WDR, 3DNR, UTC, OSD, 4 IC diode dometa do 40m, nosač sa skrivenom kablazom, napajanje DC12V / 750mA, dimenzije 275(W) * 91(H) * 80(D)mm., težina 1400g.</p>	94
LBE90HTC5005XES L		<p>1/2.8" SONY Starvis Back-illuminated CMOS sensor, AHD / TVI / CVI / CVBS vodootporna kamera rezolucije 5 megapiksela, AHD: 5M@20fps/12.5fps, 4M/2M@25fps, TVI: 5M@20fps/12.5fps, 4M/2M@25fps, CVI: 5M@20fps, 4M/2M@25fps, motorizovani varifokalni objektiv 2.7-13.5 mm, IR-CUT, IP67, WDR, 3DNR, UTC, OSD, Starlight, 6 IC dioda dometa do 60m, nosač sa skrivenom kablazom, napajanje DC12V / 900mA, dimenzije 179(W) x 90(H) x 90(D)mm, težina 1400g.</p>	101
B245		<p>Metalnii zidni G-nosač, dimenzije 245(W) x 160(D) x 163(H)mm, težina 2.1kg. Kompatibilan sa modelima: LVDB, LVDH, LVDC45, LIRAB, LVWDB20, LVWDC20, LIRDC, LIRDCA, LIRDNT, LMDC</p>	26
B131		<p>Univerzalna dozna za kamere. Razvodna kutija namenjena za spoljnu montažu. Mogućnost smeštanja konektora za povezivanje. Dimenzija dozne 131x131x51 mm.</p>	5.2
Plastično plafonsko podnožje		<p>Univerzalna duboka plastična osnova za dome kamere, dimenzija Ø14cm i dubine 3.7cm za smestaj video baluna, konektora, napajanja ...</p>	3.2
Kućište kamere B200		<p>Duboka metalna osnova za bullet kamere Ø 12cm dubine 4cm, pogodna za smestaj video baluna, konektora, napajanja ...</p>	11




AHD kamere 8 Mpix			
AC-2180		1/2.8" SONY IMX415 CMOS sensor, AHD / TVI / CVI vodootporna kamera rezolucije 8 megapiksela, AHD :4K@15fps, 4M / 2M@30fps, TVI : 4K@15fps, 4M / 2M@30fps; CVI : 4K@15fps, 4M / 2M@30fps, megapikselni objektiv 3.6mm, IR-CUT, IP67, WDR, 3DNR, UTC, OSD , 18 IC dioda dometa do 20m, napajanje DC12V / 550mA, dimenzije $\Phi 93 \times 74$ (H) mm, težina 400g	79
AC-3180		1/2.8" SONY IMX415 CMOS sensor, AHD / TVI / CVI vodootporna kamera rezolucije 8 megapiksela, AHD :4K@15fps, 4M / 2M@30fps, TVI : 4K@15fps, 4M / 2M@30fps; CVI : 4K@15fps, 4M / 2M@30fps, motorizovani varifokalni objektiv 3.3-12 mm, IR-CUT, IP67, WDR, 3DNR, UTC, OSD , 24 IC dioda dometa do 30m, napajanje DC12V / 750mA, dimenzije $\Phi 120 \times 98$ (H) mm, težina 800g	116
HDD			
HDD-1T		WD PURPLE HDD, 1TB	upit
HDD-2T		WD PURPLE HDD, 2TB	upit
HDD-4T		WD PURPLE HDD, 4TB	upit
Memorijske kartice			
WD Purple SC QD102 64GB		MicroSD kartica kapaciteta 64GB SDA 6.0, 3D NAND tehnologija, radna temperatura -25 C° to 85C°, Speed Class 10 UHS Speed Class 1 (U1), Write/Read 60/100 MB/s	upit
WD Purple SC QD102 128GB		MicroSD kartica kapaciteta 128GB High Endurance CCTV SDA 6.0, 3D NAND tehnologija, radna temperatura -25 C° to 85C°, Speed Class 10 UHS Speed Class 1 (U1), Write/Read 60/100 MB/s	upit
WD Purple SC QD102 256GB		MicroSD kartica kapaciteta 256GB Ultra Endurance CCTV SDA 6.0, 3D NAND tehnologija, radna temperatura -25 C° to 85C°, Speed Class 10 UHS Speed Class 1 (U1), Write/Read 60/100MB/s	upit
Video baluni			
CF-201		Pasivni video Balun za prenos video signala putem UTP CAT5/5E/6 kabla, kompatibilan sa AHD / TVI / CVI / CVBS , maksimalna dužina do 400m za AHD/CVI odnosno 300m za TVI/CVBS, podržane rezolucije 720P / 960P / 1080P / 3MP / 4MP / 5MP / 8MP . Cena je za par.	7.5
NT-621A / (STK 213B+)		Pasivni video Balun za prenos audio/video signala i napajanja putem UTP kabla, maksimalna dužina kabla do 100 metara. Cena za par.	6.5
STK204LL		4-kanalni pasivni video balun za prenos video signala putem UTP kabla, lak za montažu, ulazni konektor RJ 45, mogućnost montaže na zid	11
NT-2401 T		Aktivni transmiter za prenos jednog video signala putem UTP kabla. Max dometa 2400 metara. 12 V DC .	16
NT-2401 R		Aktivni risiver za prijem jednog video signala putem UTP kabla 12 V DC .	19
NT-2504 R		Aktivni risiver za prijem 4 video signala putem UTP kabla.	60
Nosачi i kućišta			
SAB-01B		Pokretni plastični nosač kamera u crnoj boji, dužina 130mm.	1
SAB-07		Pokretni metalni nosač za YC seriju kamera.	1
SAB-06-B		Pokretni metalni nosač dužine 170 mm.	1
EJWM 100		Metalni nosač za dome antivandal kamere	11
GL 610		Kućište za unutrašnje / spoljasnje za montažu u spuštenu plafon, dimenzije 125(W) x 100(H) x 335(L)mm.	8.0
GL 208		Nosač za kućište GL619 sa skrivenom kablovom.	11
Napajanja			
BF20W		Quick Charge 3.0 punjač USB A / USB C, AC Ulaz : 100~240V 50/60Hz, Izlaz : 20W max, USB-C: 5V-3A, 9V-2.22A, 12V-1.67A, USB-A: 5V 3A, 9V-2A, 12V-1.5A, USB-C + USB-A: 5V-3A	5
HTD-CVT1202000		Pretvarač 24VAC-12VDC, ulazni napon AC 20~24V, izlazni napon : 12V DC / 2A, dimenzije 61.5*33*24.5mm, težina 46.6gr.	8

HT1000		Adapter (switch) Ulaz : 100~240V AC Izlaz : 12V DC / 1A, dimenzije 96*47*30, težina 115gr.	6
HT2000-D		Adapter (switch) Ulaz : 100~240V AC Izlaz : 12V DC / 2A, dimenzije 96*47*30, težina 130gr.	7
HT2000V		Adapter (switch) Ulaz : 100~240V AC Izlaz : 12V DC / 2A, dimenzije 83*43*68, težina 110gr.	7.5
HT24W		BOX napajanje za kamere, ulaz: 100~240V AC, Izlaz: 12~13V DC / 2A. Regulacija izlaznog napona. Dimenzije 85*58*34mm, težina 130gr.	11
HT2000-W		Adapter (switch) za spoljnu montažu, ulaz: 100~240V AC Izlaz: 12V DC / 2A, dimenzije 84.8*42*136.5mm, težina 170.9gr, radna temperatura -20—60C.	10
HT3000		Adapter (switch) Ulaz : 100~240V AC Izlaz : 12V DC / 3A, dimenzije 125*50*30, težina 250gr.	11
HT3000V		Adapter (switch) Ulaz : 100~240V AC Izlaz : 12V DC / 3A, dimenzije 85*46*68, težina 250gr.	10
HT5000		Adapter (switch) Ulaz : 100~240V AC Izlaz : 12V DC / 5A, dimenzije 119.4*53*39, težina 372gr.	16
HT1205000-4		Cetvorokanalni adapter za napajanje, ulaz: AC 100~240V, izlaz: 11,8~15V DC / 5A. Regulacija izlaznog napona. Dimenzije 138.6*54.8*37mm, težina 404gr.	19
HT60W		BOX napajanje za kamere, ulaz: 100~220V AC, Izlaz: 11,8~14V DC / 5A. Regulacija izlaznog napona. Dimenzije 159.5*98*41.9mm, težina 407gr.	21
HT120W (24V)		BOX napajanje, ulaz: 100~220V AC, Izlaz: 24V DC / 5A . Regulacija izlaznog napona. Dimenzije 159.5*98*41.9mm, težina 407gr.	21
HT120W		BOX napajanje za kamere, ulaz: 100~220V AC, Izlaz: 11~16V DC / 10A. Regulacija izlaznog napona. Dimenzije 159.5*98*41.9mm, težina 407gr.	24
HTD120W-B		BOX napajanje za kamere, ulaz: 100~220V AC, Izlaz: 12~14V DC / 10A. Regulacija izlaznog napona u opsegu od 12 do 15V. Mogućnost priključenja backup baterije. Dimenzije 158*99*43mm, težina 430gr.	39
CP1204-3A-B		Cetvorokanalno BOX napajanje za kamere, možuce dodavanje back-up akumulatora 12V 7Ah , ulaz: 90~220V AC, Izlaz: DC12V+/-5% DC / 3A , dimenzije 265x205x90mm, težina 1,9kg. Isporucuje se bez akumulatora.	47
HT1218-10A		Osamnaestokanalno BOX napajanje za kamere, ulaz: 100~220V AC, Izlaz: 12~14V DC / 10A, max 1.1A po kanalu. Regulacija izlaznog napona u opsegu od 12 do 16V. Dimenzije 246*208*52mm, težina 1.61 Kg.	56
HT1218-20A-B		Osamnaestokanalno BOX napajanje za kamere, ulaz: 100~220V AC, Izlaz: 11~15V DC / 20A, max 2A po kanalu. Mogućnost priključenja backup baterije 12V 7Ah , regulacija izlaznog napona, ventilator za hlađenje. Dimenzije 264*206*90mm, težina 2.49 Kg.	99
HTD1217-10A-B		Sedamnaestokanalno rack mount napajanje sa displejem za prikaz radnog napona i potrosnje struje u realnom vremenu, ulaz: 100~220V AC, Izlaz: 11~15V DC / 10A, max 2A po kanalu za kanale 1~16 i 4A za kanal 17, regulacija izlaznog napona, mogućnost priključenja back-up baterije. Dimenzije 485.4 * 230 * 65.6mm (1.5U/19"), težina 2.9 Kg.	140
Mikrofoni			
AM-003		Visoko kvalitetni mikrofonski modul sa pojačavačem, napajanje 4-14 V, potrosnja 10 mA, pokriva do 50 kvm.	5
JR-501C-1		Napajanje 6-12V, potrosnja 12 mA, Izlazna impedansa 600Ω, frekventni opseg 200Hz ~ 20KHz, izlazni nivo 0~6V, pokriva do 50 kvm, kabl sa konektorima.	7
JR-502B		Visoko kvalitetni mikrofonski modul sa pojačavačem, kabl bez konektora, podešavanje osetljivosti, napajanje 6-14V, potrosnja 0.5~60 mA, Izlazna impedansa 600Ω, frekventni opseg 100Hz~6KHz, izlazni nivo 0~6V, pokriva do 100 kvm. Dimenzije 39.5 x 31 x 16 mm.	9
JR-2009		Visoko kvalitetni mikrofonski modul sa pojačavačem, podešavanje osetljivosti, napajanje 6-14V, potrosnja 0.5~60 mA, Izlazna impedansa 600Ω, fre. opseg 100Hz~6000Hz, izlazni nivo 0~6V, pokriva do 100 kvm. Dimenzije 40(H)x 69(Φ)	10
Aktivna mrežna oprema			
LS-HT412		4-portni PoE Switch, IEEE 802.3af Power over Ethernet (PoE) standard; 4 x 10/100Mbps RJ45 PoE Porta (Port 1 ~ 4) + 2 UpLink x 10/100Mbps (Port 5 ~ 6), PoE Power Budget max 60W. Dimenzije 220mm x 140mm x 40mm.	64
LS-HT812		8-portni PoE Switch, IEEE 802.3af Power over Ethernet (PoE) standard; 8 x 10/100Mbps RJ45 PoE Porta (Port 1 ~ 8) + 2 x UpLink x 10/100/1000Mbps (Port 9 ~ 10), PoE Power Budget max 100W. Dimenzije 220mm * 140mm * 40mm.	105

AVICOM
video security

AVICOM
video security

Longse

LS-HT1612		Longse	16-portni PoE Switch, IEEE802.3af, IEEE802.3at, Power over Ethernet (PoE) standard; 16 x 10/100Mbps RJ45 PoE Porta (Port 1 ~ 16) + 2 x UpLink x 10/100/1000Mbps (Port 17 ~18), PoE Power Budget max 240W. Dimenzije 290mm * 200mm * 44mm.	200
Pasivna mrežna oprema				
WS-6406A			Rek orman za zidnu montažu, 6U, 600x450x368 u kompletu sa šrafovim i maticama za postavljanje opreme, vrata sa bravicom i ključem, vrata se otvaraju do 180 stepeni, leva i desna strana se mogu skidati, otvori za prolaz kablova, na gornjoj strani se nalaze ležišta za dva 12cm ventilatora, dostupan u sivoj boji, maksimalna nosivost 60Kg, IP20	89
WS-6409A			Rek orman za zidnu montažu, 9U, 600x450x501 u kompletu sa šrafovim i maticama za postavljanje opreme, vrata sa bravicom i ključem, vrata se otvaraju do 180 stepeni, leva i desna strana se mogu skidati, otvori za prolaz kablova, na gornjoj strani se nalaze ležišta za dva 12cm ventilatora, dostupan u sivoj boji, maksimalna nosivost 80Kg, IP20	104
DN-91410			Modularni patch panel 24p, Prazan, Sivi, 1U, za rek 19" Za kategoriju 6, koristi se sa KJ 93601, KJ 93603, KJ 93606 i KJ 93615	19.8
DN-93615			Sertifikovan konektor za SFTP kabl kategorije 6 (CAT6a)	4
WS-S 1U 450			Fiksna polica, 1U (sa ušicama za kačenje na prednje raster letve) nosivost do 20Kg, dubina 250mm, za rekove dubine 450mm i 600mm, dostupna u sivoj boji	17.4
Elco SL 8M 1U			Razvodni panel 19" 220V, 8 utičnih mesta sa prekidačem Dužina napojnog kabla 2m, u crno/sivoj boji	27.5
CCTV testeri				
Tester X7MOVTADHS		AVICOM video security	CCTV tester + digitaln multimeter + optical power meter + visual fault locator, kompatibilan sa AHD / CVI / TVI / CVBS / HD-SDI i IP kamerama do rezolucije 4K (8MPix), H264&H265, Retina touch screen displej 7" rezolucije 1920 x 1200, Wi-Fi, LAN 10/100/1000 Mbps, HDMI izlaz / HDMI ulaz 4K, RJ45 TDR cable tester, RAPID onvif, POE tester, instalirane aplikacije: iVMS-4500HD, XMeye, gDMSS, EZView... izlaz DC12V 3A / DC24V 2A, Li-ion Polymer baterija 7800mAh, dimenzije 240 mm x 154mm x 46mm, težina 0.980gr.	639 FIX

Sve cene su iskazane u EUR sa obračunatim PDV-om, podložne su promenama i zavisne od odnosa DIN/EUR/USD.

Plaćanje se vrši u dinarima po važećem prodajnom kursu poslovne banke.

AMS electronic d.o.o. zadržava pravo izmene cena bez prethodne najave.

Dostupna i oprema koje nema u cenovniku - pozovite radi dogovora !

Za detaljnije informacije, molimo kontaktirajte našu službu prodaje ili posetite www.amselectronic.com