

TOPLOTNE PUMPE R32				
Model	Foto	Opis		Cena Eur
9 KW SPLIT 220V R32 AIRQSD		QBKFxFC-009SRI-WG Grejanje 2,5 -9 KW Hlađenje 2,5-7 KW Topla Voda 4,0-10 KW Maksimalna snaga 4,8 KW	Vazduh -Voda , Grejanje+ Hlađenje + Topla voda, Split system, DC Inverter Panasonic kompresor , R32 fluid, Wi-Fi konekcija, Digitalni kontroler, integrisana pumpa za vodu, trokraki ventil 3KW električni grejač, Napajanje 220 V AC	2520
16 KW SPLIT 220V R32 AIRQSD		QBKFxFC-016SRI-WG Grejanje 6,0-16 KW Hlađenje 5,0-13 KW Topla Voda 7,0- 18 KW Maksimalna snaga 7,7 KW		3400
12 KW MONO 380V R32 MACON®		KRCHRW12ZA-SBEN3 Grejanje 12KW Hlađenje 10 KW Topla Voda 12 KW Maksimalna snaga 5,5 KW	Vazduh -Voda , Grejanje+ Hlađenje + Topla voda, Monoblok, DC Inverter Panasonic kompresor , R32 fluid, Wi-Fi konekcija, Digitalni kontroler, Napajanje 380V AC	3180
18KW SPLIT 380V R32 MACON®		KRCRW18Y/S KRCRW18N Grejanje 18 KW Hlađenje 14 KW Topla Voda 15 KW Maksimalna snaga 5,15 KW	Vazduh -Voda , Grejanje+ Hlađenje + Topla voda, Split system, DC Inverter Panasonic kompresor , R32 fluid, Wi-Fi konekcija, Digitalni kontroler, Napajanje 380V AC	3700
18 KW SPLIT 380V R32		QBKFxFC-018SRII-WG Grejanje 6,5-18 KW Hlađenje 5- 14 KW Topla Voda 8 -20 KW Maksimalna snaga 8.0 KW	Vazduh -Voda , Grejanje+ Hlađenje + Topla voda, Split system, DC Inverter kompresor Panasonic , R32 fluid, Wi-Fi konekcija, Digitalni kontroler, instalirana pumpa za vodu, trokraki ventil, ekspanzioni sud 6l I 3KW električni grejač, Napajanje 380 V AC,	3700
24 KW SPLIT 380V R32		QBKFxFC-024SRII-WG Grejanje 9-26 KW Hlađenje 22 KW Topla Voda 26 KW Maksimalna snaga 12,9 KW		4380
30 KW SPLIT 380V R32		QBKFxFC-030SRII-WG Grejanje 12,5- 35 KW Hlađenje 28 KW Topla Voda 35 KW Maksimalna snaga 17,4 KW		5150
36 KW SPLIT 380V R32 MACON®		KRCRW36Y/S KRCRW36N Grejanje 36KW Hlađenje 30 KW Topla Voda 36 KW Maksimalna snaga 10,08KW	Vazduh -Voda , Grejanje+ Hlađenje + Topla voda, Split system, DC Inverter Panasonic kompresor , R32 fluid, Wi-Fi konekcija, Digitalni kontroler, Napajanje 380V AC	5880

TOPLOTNE PUMPE R290				
20 KW SPLIT 380V R290		QBKFXFC-020SBII Grejanje 8-25 KW Hlađenje 6,5 -18KW Topla Voda 8 - 25 KW Maksimalna snaga 11,7 KW	R290 DC Inverter 3 u 1 monoblok toplotna pumpa vazduh-voda, Wi-Fi konekcija, Kolor displej, ugrađena pumpa I ekspanzioni sud,Dual rotor DC kompresor, Max. temperature grejanja 75 C Max temp. Tople vode 65 C Temperatura Hlađenja 5 – 25 C Radna temperatura -25 ~45 C Priključci 5/4” Napajanje 380V, dimenzije 1138*525*1577mm,	3950
30 KW SPLIT 380V R290		QBKFXFC-030SBII Grejanje 10-31 KW Hlađenje 8 - 22KW Topla Voda 10- 32 KW Maksimalna snaga 12,5 KW		4950
BAFERI				
200 L		Bafer za akumulaciju vode zapremine 200 L, Prohrom SUS304, Rebrasti Izmenjivač prečnika 32 mm dužine 25m spiralno postavljen po obodu rezervoara, debljina izolacije 50mm, priključci 5/4“, ugrađen električni grejač 3 KW, Dimenzije 520 x 1550, težina 35 Kg		690
300 L		Prohromski Bafer za akumulaciju vode, zapremina 300 L, SUS304, debljina izolacije 50mm,Max pritisak 8 bara, Max. temperatura 85 C , priključci 5/4“, dimenzije 560mm x 1800mm (+70 nogice), težina 51 Kg		720
500 L		Prohromski Bafer za akumulaciju vode, zapremina 500 L, SUS304, debljina izolacije 50mm,Max pritisak 8 bara, Max. temperatura 85 C , priključci 5/4“,dimenzije 700mm x 1850mm (+70 nogice), težina 72Kg		1150
FAN COIL				
Model	Foto	Opis	Cena	
VEF-068VS		Kapacitet grejanja 3.6 kW Kapacitet hlađenja 5.4 kW Protok vazduha: 680m3/h(400CFM)	240	
VEF-085VS		Kapacitet grejanja 4.5 kW Kapacitet hlađenja 6.75 kW Protok vazduha: 850m3/h(500CFM)	260	
VEF-102VS		Kapacitet grejanja 5.4 kW Kapacitet hlađenja 8.1 kW Protok vazduha: 1020m3/h(600CFM)	282	
VEF-085CB		Kapacitet grejanja 4.5 kW Kapacitet hlađenja 6.75 kW Protok vazduha: 850m3/h(500CFM)	276	

VEF-136CB		Kapacitet grejanja 7.25 kW Kapacitet hlađenja 10.8 kW Protok vazduha: 1360m3/h(800CFM)	318
VCF-068BG		Kapacitet grejanja 5,4 kW Kapacitet hlađenja 3,6 kW Protok vazduha: 680m3/h(400CFM)	192
VCF068KMX		Kapacitet grejanja 5,4 kW Kapacitet hlađenja 3,6 kW Protok vazduha: 680m3/h(400CFM)	360
TERMOSTATI			
WT598-1T1		Smart Wi-Fi termostat, kontrola putem Tuya Smart Life aplikacije, displej dijagonale 3,5 inča ,7 dana programski tajmer, bežična komunikacija sa risiverom, Wi-Fi modul 2,4G u displeju, napajanje 3 x 1,5V AA ili USB tip C, napajanje risivera 220V AC, Potrošnja: < 1W , Relejni kontakt : 3A Opseg podešavanja temperature: 5~90 °C	67
WT-498 AVATTO		Smart Wi-Fi termostat, kontrola putem Tuya Smart Life aplikacije, displej dijagonale 3,5 inča ,7 dana programski tajmer, bežična komunikacija sa risiverom, Wi-Fi modul 2,4G u displeju, napajanje 2 x 1,5V AA ili USB tip C, napajanje risivera 220V AC, Potrošnja: < 1W , Relejni kontakt : 3A Opseg podešavanja temperature: 5~90 °C	62
WT-20		Smart Wi-Fi termostat Temperature Setting Accuracy: 0.5°C Temperature Display Accuracy:0.1 °C Screen Type: LED, Screen size:21mm WorkingTemperature: -5°C-50°C Self power consumption:<1W Temperature setting Range:5°C-95°C Temperature Display Range:0°C-51°C, Hysteresis : 0.5°C-10°C	38
TRV 601W 		Smart Wi-Fi radijatorski ventil sa digitalnim termostatom, Kontrola putem Tuya Smart Life aplikacije, 7 dana programski tajmer, u setu sa 6 priključnih adaptera, napajanje 3 x 1,5V	32
TWA ANC		Elektrotermalni ventil za sisteme podnog grejanja, NC-zatvoren kada nema napajanja, kontrola putem RF risivera, Napajanje 220 V, maksimalna potrošnja 2 W, dimenzije 60 x 35 mm	11